

4m Q/V Band LEO Earth Station Antenna

The Calian 4m Q/V-Band LEO Earth Station antenna combines high accuracy, high efficiency Cassegrain optics with high-speed slewing to track faster targets, including LEO and MEO satellites. The third tilt axis ensures uninterrupted tracking through overhead passes. This design approach combined with advanced manufacturing techniques results in a major step forward in affordable precision antenna design. Several different feeds can be fitted to support your band of operation. Calian's experience in ground station system engineering and integration has been incorporated into making this product better suited to a terminal or gateway application; examples include ease of maintenance for mechanical components and a hub designed to support a higher level of integration.

Specifications

General Configuration

Configuration:	Dual reflector Cassegrain design 3 axis motion (no keyhole), elevation over azimuth, with Tilt
Main reflector:	4m diameter High accuracy composite Surface accuracy < 0.008" RMS
Sub reflector:	High accuracy composite Surface accuracy < 0.002" RMS
Hub:	Up to 4 ft. diameter for RF equipment integration available upon request
Pedestal:	High stiffness reinforced pedestal
Optional:	De-icing system Environmentally controlled hub

M&C Interface

Ethernet interface for M&C and user interface

Full remote operation and monitoring with multiple tracking options

The antenna can be controlled via the provided computer software application or via a customer interface

Mechanical Performance

Pointing accuracy:	0.018°
Tracking accuracy:	< 0.0082°
Speed:	up to 15°/s in azimuth up to 15°/s in elevation
Acceleration:	up to 15°/s ² in both axis
Travel range:	±200° in azimuth (400° continuous) Up to 0°-180° in elevation
Tilt options:	Active or Fixed Tilt (up to 8.5°)
Drives:	Dual torque biased backlash-free drives in both axes

Power

Drive Systems:	200 to 240VAC and 380 to 430VAC 3-phase, frequency 50/60Hz
De-icing System:	208/220 3 phase
Auxiliary Circuits:	208VAC split phase 60 Hz 220VAC single phase 50 Hz (optional)

Optional Frequency Bands

Supports circular polarized single, dual, tri-band feeds, e.g., S to V, S/X, C/Ku, X/Ku, Ku/Ka, Q/V, C/Ku/Ka, Ka/Q/V, etc.

Tracking Options

Multiple open and closed loop tracking options include program track, NORAD TLE, IESS-412, monopulse, and step track



Environmental Performance

Temperature:	Operational -30 to +60 °C Survival -40 to +70 °C
Seismic:	0.3g horizontal and vertical
Wind speed:	Operational 72kph (45mph) Gusting up to 100 kph (62 mph) Survival, 200 kph (125 mph) in stow position
Humidity:	0 to 100% with condensation
Ice Accumulation:	30mm thick on all exposed surfaces
Corrosion:	Galvanized ASTM-A123, stainless and galvanized fasteners, multi-layer epoxy-based paint

Shipping Configuration and Features

Modular design to allow for easy shipping in standard containers or crates

Rapid deployment, assembly, and commissioning at customer site



Q-V-Band Performance

	Rx	Tx
Frequency (GHz)	37.50 – 42.50	47.20 – 52.40
Feed Ports	2CP + 2 Monopulse	2CP
Antenna Gain	Typical 61.95 dBi @42.50 GHz	Typical 63.64 dBi @52.40 GHz
Beamwidth @ -3dB	0.14°	0.11°
G/Ts at clear sky with 250 K LNA @ 20° elevation		
37.50 GHz	34.20 dB/K	
40.00 GHz	34.63 dB/K	
42.50 GHz	35.00 dB/K	
EIRP with 250W HPA		Typical 81.34 dBW @ 52.40 GHz
Power handling, per port (CW)		250 watts
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation	30.85 dB	30.85 dB
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	17 dB	17 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

Contact Rob or Mohamed today.

Rob Vance, Director, Satellite Antenna Ground Systems, T: 408-221-5728

Mohamed Saad, President, Calian InterTronic, T: 450-424-5666

E: antennas@calian.com

www.calian.com/products/antenna-systems