

7m - 9m High Performance Antenna

Calian high performance antennas are platforms intended for a wider variety of applications beyond satcom, including electronic warfare, radar, astronomy, and fast-target tracking. These antenna platforms combine high-slew-rate motion systems, and adaptable antenna interfaces to accommodate different applications and frequencies. We offer high accuracy optics with optimized reflector shaping for elevated efficiency. Advanced control systems can be adapted to user requirements, enabling a variety of tracking or targeting capabilities.

Specifications

General Configuration

Configuration:	Dual reflector Cassegrain design 2 axis motion, elevation over azimuth
Main reflector:	7 - 9m diameter Precision formed aluminum Surface accuracy < 0.008" RMS
Sub reflector:	High accuracy composite Surface accuracy < 0.002" RMS
Hub:	6 ft. diameter with additional RF equipment mounting provisions
Pedestal:	State of the art cable wrap systems with ample space for customer cables
Optional:	8 ft. diameter hub for internal RF equipment integration De-icing system Environmentally controlled hub Active 3rd Axis

M&C Interface

Ethernet interface for M&C and user interface

Full remote operation and monitoring with multiple tracking options

The antenna can be controlled via the provided computer software application or via a customer interface

Mechanical Performance

Pointing accuracy:	< 0.013°
Tracking accuracy:	< 0.0055°
Speed:	up to 15°/s in azimuth up to 15°/s in elevation
Acceleration:	up to 15°/s ² in both axis
Travel range:	±270° in azimuth (540° continuous) 0° - 90° in elevation
Tilt options:	Active or Fixed Tilt (up to 8.5°)
Drives:	Dual torque biased backlash-free drives in both axes

Power

Drive Systems:	200 to 240VAC and 380 to 430VAC 3-phase, frequency 50/60Hz
De-icing System:	208/220 3 phase
Auxiliary Circuits:	208VAC split phase 60 Hz 220VAC single phase 50 Hz (optional)

Optional Frequency Bands

Supports single, dual, and multi-band feeds, e.g., S to Ka, S/X, C/Ku, X/Ku, X/Ka, Ku/Ka, etc.

CP and LP Broadband feed options available

Tracking Options

Multiple open and closed loop tracking options include:
Program track, NORAD TLE, IESS-412,
Monopulse (optional), Step Track (optional)



Environmental Performance

Temperature:	Operational -30 to +60 °C Survival -40 to +70 °C
Seismic:	0.3g horizontal and vertical
Wind speed:	Operational 72kph (45mph) Gusting up to 100 kph (62 mph) Survival, 200 kph (125 mph) in stow position
Humidity:	0 to 100% with condensation
Ice Accumulation:	30mm thick on all exposed surfaces
Corrosion:	Galvanized ASTM-A123, stainless and galvanized fasteners, multi-layer epoxy-based paint

Shipping Configuration and Features

Modular design to allow for easy shipping in standard containers or crates

Rapid deployment, assembly, and commissioning at customer site



7m Ka-band Performance

	Rx	Tx
Frequency (GHz)	17.70 - 21.50	27.50 - 31.00
Feed Ports	2 + 2 Monopulse	2
Antenna Gain	61.6 dBi @21.5 GHz	64.5 dBi @31 GHz
Beamwidth @ -3dB	0.16°	0.11°
G/Ts at Clear Sky with 120 K LNA @ 20° Elevation		
17.70 GHz		
19.60 GHz	36.9 dB/K	
21.50 GHz	37.6 dB/K	
Power handling, per port (CW)	37.9 dB/K	
VSWR (Feed interface)		650 W
Cross Pol Isolation	1.25	1.25
Cross Pol Isolation	32.78 dB	32.78 dB
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	20 dB	20 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

7m Ku-band Performance

	Rx	Tx
Frequency (GHz)	10.70 – 12.75	12.70 – 14.50
Feed Ports	2	2
Antenna Gain	57.1 dBi @12.75 GHz	58.4 dBi @14.50 GHz
Beamwidth @ -3dB	0.27°	0.23°
G/Ts at Clear Sky with 59 K LNA @ 20° Elevation		
10.70 GHz	34.7 dB/K	
11.75 GHz	35.5 dB/K	
12.75 GHz	36.2 dB/K	
Power handling, per port (CW)		1.5 KW
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation	35 dB	35 dB
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_y$, $T_x \rightarrow T_y$	35 dB	35 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

7m X-band Performance

	Rx	Tx
Frequency (GHz)	7.25 – 7.75	7.90 – 8.40
Feed Ports	2	2
Antenna Gain	52.9 dBi @7.75 GHz	53.6 dBi @8.40 GHz
Beamwidth @ -3dB	0.42°	0.38°
G/Ts at Clear Sky with 50 K LNA @ 10° Elevation		
7.25 GHz	31.9 dB/K	
7.50 GHz	32.2 dB/K	
7.75 GHz	32.5 dB/K	
Power handling, per port (CW)		2 KW
VSWR (Feed interface)	1.30	1.30
Cross Pol Isolation	32.78 dB	32.78 dB
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_y$, $T_x \rightarrow T_y$	18 dB	18 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

7m C-band Performance

	Rx	Tx
Frequency (GHz)	3.400 – 4.200	5.725 – 6.725
Feed Ports	2	2
Antenna Gain	47.8 dBi @4.200 GHz	51.9 dBi @6.725 GHz
Beamwidth @ -3dB	0.82°	0.50°
G/Ts at Clear Sky with 30 K LNA @ 20° Elevation		
3.400 GHz	26.7 dB/K	
3.800 GHz	27.7 dB/K	
4.200 GHz	28.6 dB/K	
Power handling, per port (CW)		2.5 KW
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation	32.78 dB	32.78 dB
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	20 dB	20 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

7m S-band Performance

	Rx	Tx
Frequency (GHz)	2.170 – 2.300	1.980 – 2.120
Feed Ports	2	2
Antenna Gain	42.6 dBi @2.300 GHz	41.9 dBi @2.120 GHz
Beamwidth @ -3dB	1.40°	1.52°
G/Ts at Clear Sky with 45 K LNA @ 20° Elevation		
2.170 GHz	21.9 dB/K	
2.235 GHz	22.2 dB/K	
2.300 GHz	22.4 dB/K	
Power handling, per port (CW)		5 KW
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation	32.78 dB	32.78 dB
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	20 dB	20 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

Contact Rob or Mohamed today.

Rob Vance, Director, Satellite Antenna Ground Systems, T: 408-221-5728

Mohamed Saad, President, Calian InterTronic, T: 450-424-5666

E: antennas@calian.com

www.calian.com/products/antenna-systems